

ENHANCED STABILITY. GREATER MANEUVERABILITY. NEW CAPACITIES.

INTRODUCING THE RAYMOND 4750 WITH 3,000 AND 3,500 LB. CAPACITIES.

Ideal for tight floor applications, Raymond's new 4750 4-wheel sit-down counterbalanced trucks feature an overall width of just 37" and a turn radius of 66.3".

Designed for exceptional stability, agility, and maneuverability, the 4750 is now available with capacities of 3,000 or 3,500 lbs. to help you handle lighter loads more quickly and efficiently while optimizing your storage capacity.

FEATURES & BENEFITS

Greater Productivity

- + Integral Sideshift—standard on all 4750 trucks—allows faster, simpler pallet positioning.
- + Auto Tilt Leveling brings forks perpendicular to the mast with the touch of a button for easier, more confident load stacking and retrieval.

Superior Stability

- + Performance Stability System™ helps minimize damage to goods and facilities with automatic turn speed control, active mast control, and active rear axle swing lock.

Enhanced Ergonomics

- + Spacious, easy-to-access operator compartment includes a fully adjustable, full-suspension, cushioned seat, tilt steering wheel, and ergonomically placed controls for enhanced comfort and productivity.

Easier Maintainability

- + Heavy-duty AC motors for load handling, traveling, and steering increase uptime and decrease maintenance costs.
- + Optional tilt cylinder guard can help reduce maintenance requirements and costs in applications with shrink-wrapped pallets.



SPECIFICATIONS

	C30	C35
CAPACITY	3,000 lbs.	3,500 lbs.
TRAVEL SPEED	Travel speed 11.5 mph (loaded & unloaded) for both 36v and 48v	Travel speed 11.3 mph (loaded) for both 36v and 48v Travel speed 11.5 mph (unloaded) for both 36v and 48v
LIFT SPEED	Lift speed 84 fpm (loaded) for 36v Lift speed 124 fpm (unloaded) for 36v Lift speed 102 fpm (loaded) for 48v Lift speed 131 fpm (unloaded) for 48v	Lift speed 81 fpm (loaded) for 36v Lift speed 124 fpm (unloaded) for 36v Lift speed 99 fpm (loaded) for 48v Lift speed 131 fpm (unloaded) for 48v
TURN RADIUS	66.3"	66.3"
VOLTAGE	36v or 48v	36v or 48v

4750 CAPACITY OPTIONS

3,000 lbs.*	6,000 lbs.
3,500 lbs.*	6,500 lbs.
4,000 lbs.	8,000 lbs.*
5,000 lbs.	10,000 lbs.*
5,500 lbs.	12,000 lbs.*

* New

For more information on our highly maneuverable new 4750 truck models or how they could help increase efficiency and lower costs throughout your operation, please contact your nearest Raymond Solutions and Support Center.